## NSN 5910-01-307-5710

Electrolytic Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-307-5710

**Body Style:** 

W/o mtg facilities, terminal (s) on one end

Reliability Indicator:

Not established

**Terminal Length:** 

Between 0.094 inches and 0.156 inches

**Body Diameter:** 

Between 2.979 inches and 3.041 inches

**Body Length:** 

Between 4.078 inches and 4.202 inches

**Center To Center Distance Between Terminals Parallel To Diameter:** 

Between 1.234 inches and 1.266 inches

**Terminal Diameter:** 

0.250 inches

**Schematic Diagram Designator:** 

No common or grounded electrode (s)

**Anode Type:** 

Plain foil

**Electrical Polarization:** 

Polarized

**Capacitance Value Per Section:** 

69000.000 microfarads single section

**Nonderated Operating Temp:** 

Between -40.0 degrees celsius and 105.0 degrees celsius

Dc Leakage At Maximum Operating Temp:

11.5 milliamperes

Nonderated Continuous Voltage Rating And Type Per Section:

30.0 dc single section

**Tolerance Range Per Section:** 

-10.00/+75.00 percent single section

**Case Material:** 

Metal

**Capacitive Electrode Material:** 

Aluminum

**Equivalent Series Resistance At Reference Tempurature In Ohms:** 

0.0042

Dc Leakage At Reference Temp:

1.400 milliamperes

**Terminal Type And Quantity:** 

2 threaded hole

Shelf Life:

N/a

## NSN 5910-01-307-5710

Electrolytic Fixed Capacitor - Page 2 of 2



	• •				
In	18	<i>(</i> )+	МА	261	ıre:

--

Demilitarization:

No

Fiig:

A010b0