NSN 5910-01-307-9706

Electrolytic Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-307-9706 **Body Style:** W/o mtg facilities, terminal (s) on one end Reliability Indicator: Not established **Terminal Length:** Between 0.155 inches and 0.219 inches **Body Diameter:** 0.250 inches **Body Length:** 0.500 inches **Center To Center Distance Between Terminals Parallel To Diameter:** Between 0.235 inches and 0.265 inches **Terminal Diameter:** 0.025 inches **Schematic Diagram Designator:** No common or grounded electrode (s) **Anode Type:** Solid **Electrical Polarization:** Polarized **Capacitance Value Per Section:** 39.000 microfarads single section **Nonderated Operating Temp:** Between -55.0 degrees celsius and 85.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 10.0 dc single section **Tolerance Range Per Section:** -10.00/+10.00 percent single section **Case Material: Plastic Capacitive Electrode Material: Dissipation Factor At Reference Tempurature In Percent:** 8.000 Dc Leakage At Reference Temp: 3.000 microamperes **Terminal Surface Treatment:** Solder **Terminal Type And Quantity:** 2 uninsulated wire lead

N/a

Shelf Life:

NSN 5910-01-307-9706

Electrolytic Fixed Capacitor - Page 2 of 2



	• •				
In	18	<i>(</i>)+	МЛО	201	ure:

--

Demilitarization:

No

Fiig:

A010b0