

View Online at https://aerobasegroup.com/nsn/5910-01-308-6292

| Body Style: | |
|-----------------------|---|
| Chip type | |
| Reliability Indicato | r: |
| Not established | |
| Terminal Length: | |
| Between 0.010 inche | es and 0.040 inches |
| Body Length: | |
| Between 0.118 inche | es and 0.134 inches |
| Body Width: | |
| Between 0.055 inche | es and 0.071 inches |
| Body Height: | |
| 0.059 inches | |
| Schematic Diagran | n Designator: |
| No common or grou | nded electrode (s) |
| Capacitance Value | Per Section: |
| 10000.000 picofarac | Is single section |
| Nonderated Operat | ing Temp: |
| Between -55.0 degre | ees celsius and 125.0 degrees celsius |
| Tempurature Coeff | icient Of Capacitance Per Section In Ppm Per Deg Celsius: |
| 0.0 single section | |
| Nonderated Contin | uous Voltage Rating And Type Per Section: |
| 50.0 dc single sectio | n |
| Tolerance Of Temp | ourature Coefficient Per Section In Ppm Per Deg Celsius: |
| -30.0/+30.0 single se | ection |
| Tolerance Range P | er Section: |
| -2.00/+2.00 percent | single section |
| Case Material: | |
| Ceramic | |
| Terminal Surface T | reatment: |
| Solder | |
| Terminal Type And | Quantity: |
| 2 bonding pad | |
| Shelf Life: | |
| N/a | |
| Unit Of Measure: | |
| Demilitarization: | |
| No | |
| Fiig: | |
| A010b0 | |