

View Online at <https://aerobasegroup.com/nsn/5910-01-308-6907>

**Body Style:**

W/o mtg facilities terminal (s) on one surface

**Reliability Indicator:**

Not established

**Terminal Length:**

1.250 inches

**Body Length:**

0.290 inches

**Body Width:**

0.290 inches

**Body Height:**

0.090 inches

**Center To Center Distance Between Terminals Parallel To Length:**

0.200 inches

**Terminal Diameter:**

Between 0.023 inches and 0.029 inches

**Unthreaded Mounting Hole Diameter:**

Between 0.343 inches and 0.350 inches

**Schematic Diagram Designator:**

No common or grounded electrode (s)

**End Application:**

Guidance and control group

**Mounting Facility Type And Quantity:**

2 unthreaded mounting holes

**Section Quantity:**

5

**Insulation Resistance At Maximum Operating Temp:**

10000.0 megohms

**Capacitance Value Per Section:**

3300.000 picofarads all sections

**Voltage Temperature Limits Per Section In Percent Capacitance Change:**

-15.0/+15.0 without voltage applied all sections

**Nonderated Operating Temp:**

Between -55.0 degrees celsius and 125.0 degrees celsius

**Nonderated Continuous Voltage Rating And Type Per Section:**

200.0 dc all sections

**Tolerance Range Per Section:**

-10.00/+10.00 percent all sections

**Case Material:**

Plastic

**Insulation Resistance At Reference Temp:**

100000.0 megohms

**Dissipation Factor At Reference Temperature In Percent:**

2.500

**Terminal Surface Treatment:**

Solder

**Special Features:**

Capacitors mtd in container 2.170 in. O/a lg; 0.750 in. O/a h; 0.750 in. O/a w

**Terminal Type And Quantity:**

2 uninsulated wire lead

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A010b0