NSN 5910-01-308-7845

Body Style:

2 threaded hole

Electrolytic Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-308-7845

| W/o mtg facilities, terminal (s) on one end |
|---|
| Reliability Indicator: |
| Not established |
| Terminal Length: |
| 0.250 inches |
| Body Diameter: |
| 1.453 inches |
| Body Length: |
| 5.750 inches |
| Center To Center Distance Between Terminals Parallel To Diameter: |
| 0.500 inches |
| Terminal Diameter: |
| 0.190 inches |
| Schematic Diagram Designator: |
| No common or grounded electrode (s) |
| Anode Type: |
| Plain foil |
| Electrical Polarization: |
| Polarized |
| End Application: |
| 6625-01-226-5448 voltage standard |
| Capacitance Value Per Section: |
| 34000.000 microfarads single section |
| Nonderated Operating Temp: |
| Between -40.0 degrees celsius and 85.0 degrees celsius |
| Dc Leakage At Maximum Operating Temp: |
| 20000.0 microamperes |
| Nonderated Continuous Voltage Rating And Type Per Section: |
| 15.0 dc single section |
| Tolerance Range Per Section: |
| -10.00/+75.00 percent single section |
| Case Material: |
| Metal |
| Capacitive Electrode Material: |
| Aluminum |
| Dc Leakage At Reference Temp: |
| 4.000 microamperes |
| Case Insulation Material: |
| Plastic |
| Terminal Type And Quantity: |

NSN 5910-01-308-7845

Electrolytic Fixed Capacitor - Page 2 of 2



| _ | | | | | |
|---|----|------|---|--------|--|
| c | hο | JIF. | | .ife: | |
| J | | | _ | .II C. | |

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A010b0