NSN 5910-01-309-2362



Electrolytic Fixed Capacitor - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5910-01-309-2362 **Body Style:** W/o mtg facilities, axial terminals Reliability Indicator: Not established **Terminal Length:** 1.500 inches **Body Diameter:** Between 0.656 inches and 0.718 inches **Body Length:** Between 2.710 inches and 2.790 inches **Terminal Diameter:** 0.032 inches **Schematic Diagram Designator:** No common or grounded electrode (s) **Anode Type:** Plain foil **Electrical Polarization:** Polarized **Capacitance Value Per Section:** 600.000 microfarads single section **Nonderated Operating Temp:** Between -20.0 degrees celsius and 85.0 degrees celsius Dc Leakage At Maximum Operating Temp: 5.0 microamperes Nonderated Continuous Voltage Rating And Type Per Section: 40.0 dc single section **Tolerance Range Per Section:** -10.00/+75.00 percent single section **Case Material:** Metal **Capacitive Electrode Material: Dissipation Factor At Reference Tempurature In Percent:** 0.450 Dc Leakage At Reference Temp:

1.000 microamperes

Terminal Surface Treatment:

Solder

Case Insulation Material:

Plastic

Terminal Type And Quantity:

2 uninsulated wire lead

NSN 5910-01-309-2362

Electrolytic Fixed Capacitor - Page 2 of 2



_					
c	hο	JIF.		.ife:	
J			_	.II C.	

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A010b0