## NSN 5910-01-310-4583

Electrolytic Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-310-4583

view Online at https://acrobasegroup.com/nsi//05/10-01-5/10-4505
Body Style:
W/o mtg facilities, terminal (s) on one end
Dummy Terminal Quantity:
1
Reliability Indicator:
Not established
Terminal Length:
0.250 inches
Body Diameter:
1.440 inches
Body Length:
2.330 inches
Center To Center Distance Between Terminals Parallel To Diameter
Between 0.484 inches and 0.516 inches
Terminal Diameter:
0.064 inches
Schematic Diagram Designator:
No common or grounded electrode (s)
Anode Type:
Plain foil
Impedance At Minimum Operating Tempurature In Ohms:
20.0
Electrical Polarization:
Polarized
End Application:
6625-01-255-1620 test set, electra
Capacitance Value Per Section:
17000.000 microfarads single section
Nonderated Operating Temp:
Between -40.0 degrees celsius and 95.0 degrees celsius
Nonderated Continuous Voltage Rating And Type Per Section:
15.0 dc single section
Tolerance Range Per Section:
-10.00/+75.00 percent single section
Case Material:
Metal
Capacitive Electrode Material:
Aluminum
Equivalent Series Resistance At Reference Tempurature In Ohms:

Dc Leakage At Reference Temp:

20000.000 microamperes

46.60

## NSN 5910-01-310-4583 Electrolytic Fixed Capacitor - Page 2 of 2



Terminal Surface Treatment:
Solder
Case Insulation Material:
Plastic
Terminal Type And Quantity:
3 tab, solder lug
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A010b0