## NSN 5910-01-310-5394

Electrolytic Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-310-5394

**Body Style:** W/o mtg facilities, terminal (s) on one end Reliability Indicator: Not established **Terminal Length:** 25.0 millimeters **Body Diameter:** 12.5 millimeters **Body Length:** 42.5 millimeters **Center To Center Distance Between Terminals Parallel To Diameter:** 5.0 millimeters **Terminal Diameter:** 0.6 millimeters **Schematic Diagram Designator:** No common or grounded electrode (s) **Anode Type:** Plain foil **Impedance At Minimum Operating Tempurature In Ohms:** 0.15 **Electrical Polarization:** Polarized **Capacitance Value Per Section:** 220.000 microfarads single section **Nonderated Operating Temp:** Between -55.0 degrees celsius and 105.0 degrees celsius Dc Leakage At Maximum Operating Temp: 1.280 microamperes Nonderated Continuous Voltage Rating And Type Per Section: 50.0 dc single section **Tolerance Range Per Section:** -10.00/+100.00 percent single section **Case Material:** Metal **Capacitive Electrode Material:** Aluminum **Equivalent Series Resistance At Reference Tempurature In Ohms:** 0.40 Dc Leakage At Reference Temp: 2.000 microamperes

Solder

**Terminal Surface Treatment:** 

## NSN 5910-01-310-5394 Electrolytic Fixed Capacitor - Page 2 of 2



Case Insulation Material:
Plastic
Terminal Type And Quantity
2 uninsulated wire lead
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A010b0