## NSN 5910-01-310-6025

Electrolytic Fixed Capacitor - Page 1 of 2



Body Style:
W/o mtg facilities, terminal (s) on one end
Reliability Indicator:
Not established
Terminal Length:
5.0 millimeters
Body Diameter:
4.0 millimeters
Body Length:
7.0 millimeters
Center To Center Distance Between Terminals Parallel To Diameter:
1.5 millimeters
Terminal Diameter:
0.5 millimeters
Schematic Diagram Designator:
No common or grounded electrode (s)
Anode Type:
Plain foil
Impedance At Minimum Operating Tempurature In Ohms:
2.0
Floatrical Palarinations
Electrical Polarization:
Polarized
Polarized
Polarized End Application:
Polarized End Application: 6625-01-255-4547 voltmeter
Polarized  End Application:  6625-01-255-4547 voltmeter  Capacitance Value Per Section:
Polarized  End Application: 6625-01-255-4547 voltmeter  Capacitance Value Per Section: 1.000 microfarads single section
Polarized  End Application: 6625-01-255-4547 voltmeter  Capacitance Value Per Section: 1.000 microfarads single section  Nonderated Operating Temp:
Polarized  End Application: 6625-01-255-4547 voltmeter  Capacitance Value Per Section: 1.000 microfarads single section  Nonderated Operating Temp: Between -40.0 degrees celsius and 85.0 degrees celsius
Polarized  End Application: 6625-01-255-4547 voltmeter  Capacitance Value Per Section: 1.000 microfarads single section  Nonderated Operating Temp: Between -40.0 degrees celsius and 85.0 degrees celsius  Nonderated Continuous Voltage Rating And Type Per Section:
Polarized  End Application: 6625-01-255-4547 voltmeter  Capacitance Value Per Section: 1.000 microfarads single section  Nonderated Operating Temp: Between -40.0 degrees celsius and 85.0 degrees celsius  Nonderated Continuous Voltage Rating And Type Per Section: 50.0 dc single section
Polarized  End Application: 6625-01-255-4547 voltmeter  Capacitance Value Per Section: 1.000 microfarads single section  Nonderated Operating Temp: Between -40.0 degrees celsius and 85.0 degrees celsius  Nonderated Continuous Voltage Rating And Type Per Section: 50.0 dc single section  Tolerance Range Per Section:
Polarized End Application: 6625-01-255-4547 voltmeter Capacitance Value Per Section: 1.000 microfarads single section Nonderated Operating Temp: Between -40.0 degrees celsius and 85.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 50.0 dc single section Tolerance Range Per Section: -20.00/+20.00 percent single section
Polarized End Application: 6625-01-255-4547 voltmeter Capacitance Value Per Section: 1.000 microfarads single section Nonderated Operating Temp: Between -40.0 degrees celsius and 85.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 50.0 dc single section Tolerance Range Per Section: -20.00/+20.00 percent single section Case Material:
Polarized End Application: 6625-01-255-4547 voltmeter Capacitance Value Per Section: 1.000 microfarads single section Nonderated Operating Temp: Between -40.0 degrees celsius and 85.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 50.0 dc single section Tolerance Range Per Section: -20.00/+20.00 percent single section Case Material: Metal
End Application: 6625-01-255-4547 voltmeter  Capacitance Value Per Section: 1.000 microfarads single section  Nonderated Operating Temp: Between -40.0 degrees celsius and 85.0 degrees celsius  Nonderated Continuous Voltage Rating And Type Per Section: 50.0 dc single section  Tolerance Range Per Section: -20.00/+20.00 percent single section  Case Material:  Metal  Capacitive Electrode Material:
End Application: 6625-01-255-4547 voltmeter Capacitance Value Per Section: 1.000 microfarads single section Nonderated Operating Temp: Between -40.0 degrees celsius and 85.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 50.0 dc single section Tolerance Range Per Section: -20.00/+20.00 percent single section Case Material: Metal Capacitive Electrode Material: Aluminum
End Application: 6625-01-255-4547 voltmeter  Capacitance Value Per Section: 1.000 microfarads single section  Nonderated Operating Temp: Between -40.0 degrees celsius and 85.0 degrees celsius  Nonderated Continuous Voltage Rating And Type Per Section: 50.0 dc single section  Tolerance Range Per Section: -20.00/+20.00 percent single section  Case Material:  Metal  Capacitive Electrode Material:  Aluminum  Dissipation Factor At Reference Tempurature In Percent:

Solder

**Terminal Surface Treatment:** 

## NSN 5910-01-310-6025 Electrolytic Fixed Capacitor - Page 2 of 2



Case insulation Material:
Plastic
Terminal Type And Quantity:
2 uninsulated wire lead
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A010b0