## NSN 5910-01-310-9268

Ceramic Dielectric Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-310-9268

**Body Style:** W/o mtg facilities terminal (s) on one surface **Reliability Indicator:** Not established **Terminal Length:** 1.000 inches **Body Length:** 0.300 inches **Body Width:** 0.300 inches **Body Height:** 0.100 inches Center To Center Distance Between Terminals Parallel To Length: Between 0.185 inches and 0.215 inches **Terminal Diameter:** Between 0.010 inches and 0.040 inches **Schematic Diagram Designator:** No common or grounded electrode (s) **Insulation Resistance At Maximum Operating Temp:** 10000.0 megohms **Capacitance Value Per Section:** 2223.000 picofarads single section **Nonderated Operating Temp:** Between 0.0 degrees celsius and 125.0 degrees celsius Tempurature Coefficient Of Capacitance Per Section In Ppm Per Deg Celsius: 0.0 single section Nonderated Continuous Voltage Rating And Type Per Section: 50.0 dc single section **Tolerance Of Tempurature Coefficient Per Section In Ppm Per Deg Celsius:** -30.0/+30.0 single section **Tolerance Range Per Section:** -1.00/+1.00 percent single section **Case Material:** Plastic Insulation Resistance At Reference Temp: 100000.0 megohms **Dissipation Factor At Reference Tempurature In Percent:** 0.150 **Terminal Surface Treatment:** Solder

2 uninsulated wire lead

**Terminal Type And Quantity:** 

## NSN 5910-01-310-9268

Ceramic Dielectric Fixed Capacitor - Page 2 of 2



_					
c	hο	JIF.		.ife:	
J			_	.II C.	

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A010b0