NSN 5910-01-311-0826

Electrolytic Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-311-0826

View Online at https://aerobasegroup.com/nsn/5910-01-311-0826
Body Style:
W/o mtg facilities, axial terminals
Reliability Indicator:
Established
Reliability Failure Rate Level In Percent:
0.100
Terminal Length:
2.500 inches
Body Diameter:
1.000 inches
Body Length:
Between 3.125 inches and 3.328 inches
Terminal Diameter:
0.040 inches
Schematic Diagram Designator:
Electrod (s) grounded to case, w/gnd terminal
Electrical Polarization:
Polarized
Features Provided:
Burn in
Capacitance Value Per Section:
2700.000 microfarads single section
Nonderated Operating Temp:
Between -55.0 degrees celsius and 105.0 degrees celsius
Nonderated Continuous Voltage Rating And Type Per Section:
30.0 dc single section
Tolerance Range Per Section:
-10.00/+75.00 percent single section
Case Material:
Metal
Capacitive Electrode Material:
Aluminum
Case Insulation Material:
Plastic
Test Data Document:
81349-mil-c-39018 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Terminal Type And Quantity:

2 uninsulated wire lead

_ _

Specification Data:

81349-mil-c-39018/3 government specification

Shelf Life:

N/a

NSN 5910-01-311-0826

Electrolytic Fixed Capacitor - Page 2 of 2



		• •			
ш	ın	10	<i>(</i>)+	Measure:	

--

Demilitarization:

No

Fiig:

A010b0