## NSN 5910-01-311-2495

Electrolytic Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-311-2495 **Body Style:** W/o mtg facilities, terminal (s) on one end Reliability Indicator: Established **Reliability Failure Rate Level In Percent:** 0.100 **Body Diameter:** 1.375 inches **Body Length:** 2.125 inches **Center To Center Distance Between Terminals Parallel To Diameter:** 0.500 inches **Schematic Diagram Designator:** No common or grounded electrode (s) **Electrical Polarization:** Polarized **Capacitance Value Per Section:** 14000.000 microfarads single section **Nonderated Operating Temp:** Between -55.0 degrees celsius and 105.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 10.0 dc single section **Tolerance Range Per Section:** -10.00/+75.00 percent single section **Case Material:** Metal **Capacitive Electrode Material:** Aluminum **Case Insulation Material: Plastic Test Data Document:** 81349-mil-c-39018 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). **Terminal Type And Quantity:** 2 threaded hole **Specification Data:** 81349-mil-c-39018/10 government specification Shelf Life: N/a

No

**Unit Of Measure:** 

**Demilitarization:** 

## NSN 5910-01-311-2495

Electrolytic Fixed Capacitor - Page 2 of 2



Fiig:

A010b0