

View Online at https://aerobasegroup.com/nsn/5910-01-311-5315

Reliability Indicator:
Not established
Schematic Diagram Designator:
No common or grounded electrode (s)
Capacitance Value Per Section:
0.680 microfarads single section
Nonderated Operating Temp:
Between -40.0 degrees celsius and 85.0 degrees celsius
Nonderated Continuous Voltage Rating And Type Per Section:
100.0 dc single section
Tolerance Range Per Section:
-10.00/+10.00 percent single section
Case Material:
Plastic
Insulation Resistance At Reference Temp:
10000.0 megohms
10000.0 megohms Power Factor At Reference Tempurature In Percent:
5
Power Factor At Reference Tempurature In Percent:
Power Factor At Reference Tempurature In Percent: 0.010
Power Factor At Reference Tempurature In Percent: 0.010 Terminal Surface Treatment:
Power Factor At Reference Tempurature In Percent: 0.010 Terminal Surface Treatment: Solder
Power Factor At Reference Tempurature In Percent: 0.010 Terminal Surface Treatment: Solder Shelf Life:
Power Factor At Reference Tempurature In Percent: 0.010 Terminal Surface Treatment: Solder Shelf Life: N/a
Power Factor At Reference Tempurature In Percent: 0.010 Terminal Surface Treatment: Solder Shelf Life: N/a Unit Of Measure:
Power Factor At Reference Tempurature In Percent: 0.010 Terminal Surface Treatment: Solder Shelf Life: N/a Unit Of Measure:
Power Factor At Reference Tempurature In Percent: 0.010 Terminal Surface Treatment: Solder Shelf Life: N/a Unit Of Measure: Demilitarization:
Power Factor At Reference Tempurature In Percent: 0.010 Terminal Surface Treatment: Solder Shelf Life: N/a Unit Of Measure: Demilitarization: No