NSN 5910-01-312-9116

Ceramic Dielectric Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-312-9116 **Body Style:** Chip type **Reliability Indicator:** Not established **Terminal Length:** Between 0.3 millimeters and 0.8 millimeters **Body Length:** Between 1.7 millimeters and 2.3 millimeters **Body Width:** Between 1.0 millimeters and 1.6 millimeters **Body Height:** 1.5 millimeters **Schematic Diagram Designator:** No common or grounded electrode (s) **Capacitance Value Per Section:** 2.700 picofarads single section **Nonderated Operating Temp:** Between -55.0 degrees celsius and 125.0 degrees celsius Tempurature Coefficient Of Capacitance Per Section In Ppm Per Deg Celsius: 0.0 single section Nonderated Continuous Voltage Rating And Type Per Section: 50.0 dc single section **Tolerance Of Tempurature Coefficient Per Section In Ppm Per Deg Celsius:** -30.0/+30.0 single section **Tolerance Range Per Section:** -0.50/+0.50 picofarads single section Case Material: Ceramic **Insulation Resistance At Reference Temp:** 10000.0 megohms **Power Factor At Reference Tempurature In Percent:** 0.001 **Terminal Surface Treatment:** Palladium and silver **Precious Material And Location:** Terminal surfaces palladium and terminal surfaces silver **Terminal Type And Quantity:** 2 bonding pad Shelf Life: N/a

Unit Of Measure:

NSN 5910-01-312-9116

Ceramic Dielectric Fixed Capacitor - Page 2 of 2



Demilitarization:

No

Fiig:

A010b0