## NSN 5910-01-313-0443

Electrolytic Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-313-0443 **Body Style:** W/o mtg facilities, terminal (s) on one end Reliability Indicator: Not established **Terminal Length:** 0.980 inches **Body Diameter:** 0.315 inches **Body Length:** 0.453 inches **Center To Center Distance Between Terminals Parallel To Diameter:** 0.138 inches **Terminal Diameter:** 0.020 inches **Schematic Diagram Designator:** No common or grounded electrode (s) **Anode Type:** Plain foil **Impedance At Minimum Operating Tempurature In Ohms:** 2.0 **Electrical Polarization:** Polarized **Capacitance Value Per Section:** 220.000 microfarads single section **Nonderated Operating Temp:** Between -40.0 degrees celsius and 85.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 16.0 dc single section **Tolerance Range Per Section:** -10.00/+10.00 percent single section Case Material: Metal **Capacitive Electrode Material:** Aluminum **Dissipation Factor At Reference Tempurature In Percent:** 0.120 **Terminal Surface Treatment:** Solder **Case Insulation Material: Plastic** 

Terminal Type And Quantity:

2 uninsulated wire lead

## NSN 5910-01-313-0443

Electrolytic Fixed Capacitor - Page 2 of 2



| _ |   |            |   |    |    |
|---|---|------------|---|----|----|
| • | n | <b>0</b> 1 | • | 12 | e: |
|   |   |            |   |    |    |

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A010b0