## NSN 5910-01-313-2087

Plastic Dielectric Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-313-2087 **Body Style:** W/o mtg facilities terminal (s) on one surface **Reliability Indicator:** Not established **Terminal Length:** Between 0.157 inches and 0.197 inches **Body Length:** 0.532 inches **Body Width:** 0.512 inches **Body Height:** 0.217 inches Center To Center Distance Between Terminals Parallel To Length: 0.375 inches **Terminal Diameter:** 0.025 inches **Schematic Diagram Designator:** No common or grounded electrode (s) **Internal Electrical Connection Type:** Extended foil **Capacitance Value Per Section:** 0.0033 microfarads single section **Nonderated Operating Temp:** Between -55.0 degrees celsius and 85.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 630.0 dc single section **Tolerance Range Per Section:** -10.00/+10.00 percent single section Case Material: **Plastic Insulation Resistance At Reference Temp:** 10000.0 megohms **Dissipation Factor At Reference Tempurature In Percent:** 0.500 **Terminal Surface Treatment:** Solder **Dielectric Material:** Plastic polypropylene **Terminal Type And Quantity:** 

2 uninsulated wire lead Shelf Life:

N/a

## NSN 5910-01-313-2087

Plastic Dielectric Fixed Capacitor - Page 2 of 2



ш	ın	10	<i>(</i> )+	Measure:	

--

Demilitarization:

No

Fiig:

A010b0