

View Online at <https://aerobasegroup.com/nsn/5910-01-314-3059>

Body Style:

W/o mtg facilities terminal (s) on one surface

Reliability Indicator:

Not established

Terminal Length:

Between 0.157 inches and 0.163 inches

Body Length:

0.289 inches

Body Width:

0.399 inches

Body Height:

0.202 inches

Center To Center Distance Between Terminals Parallel To Length:

0.200 inches

Terminal Diameter:

0.024 inches

Schematic Diagram Designator:

No common or grounded electrode (s)

End Application:

Lcac; helicopter, carrier based asw; helicopter, search and rescue; helicopter, usc g; los angeles class ssn (688); ticongeroga class cg (47); spruance class dd (963); forrestal class cv; nimitz class cvn

Capacitance Value Per Section:

0.470 microfarads single section

Nonderated Operating Temp:

Between -55.0 degrees celsius and 100.0 degrees celsius

Nonderated Continuous Voltage Rating And Type Per Section:

63.0 dc single section

Criticality Code Justification:

Feat

Tolerance Range Per Section:

-5.00/+5.00 percent single section

Case Material:

Plastic

Insulation Resistance At Reference Temp:

1000.0 megohm-microfarads

Dissipation Factor At Reference Temperature In Percent:

1.000

Terminal Surface Treatment:

Solder

Dielectric Material:

Plastic polyester

Special Features:

Weapon system essential

Terminal Type And Quantity:

2 uninsulated wire lead

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A010b0