## NSN 5910-01-315-6331

Plastic Dielectric Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-315-6331
Body Style:
W/thd bushing mtg, terminals on opposite ends
Reliability Indicator:
Not established
Terminal Length:
0.340 inches
Body Diameter:
Between 0.735 inches and 0.765 inches
Body Length:
Between 1.720 inches and 1.780 inches
Continuous Current Rating In Amps:
50.0
Terminal Diameter:
Between 0.092 inches and 0.097 inches
Schematic Diagram Designator:
Two terminals common to one electrode
End Application:
An/sqs-53c rev a
Features Provided:
Hermetically sealed case
Capacitance Value Per Section:
47000.000 picofarads single section
Nonderated Operating Temp:
Between -55.0 degrees celsius and 125.0 degrees celsius
Nonderated Continuous Voltage Rating And Type Per Section:
440.0 ac-rms single section and 600.0 dc single section
Tolerance Range Per Section:
-10.00/+10.00 percent single section
Case Material:
Metal
Insulation Resistance At Reference Temp:
30000.0 megohm-microfarads
Dissipation Factor At Reference Tempurature In Percent:
1.000
Case Insulation Material:
Plastic
Terminal Type And Quantity:
2 insulated wire lead
Shelf Life:
N/a
Unit Of Measure:

--

## NSN 5910-01-315-6331

Plastic Dielectric Fixed Capacitor - Page 2 of 2



Demilitarization:

No

Fiig:

A010b0