

View Online at <https://aerobasegroup.com/nsn/5910-01-316-0922>

**Body Style:**

W/o mtg facilities, terminal (s) on one end

**Reliability Indicator:**

Not established

**Terminal Length:**

Between 0.500 inches and 1.000 inches

**Body Diameter:**

0.250 inches

**Body Length:**

0.360 inches

**Center To Center Distance Between Terminals Parallel To Diameter:**

Between 0.070 inches and 0.130 inches

**Terminal Diameter:**

0.020 inches

**Schematic Diagram Designator:**

No common or grounded electrode (s)

**Anode Type:**

Solid

**Electrical Polarization:**

Polarized

**Capacitance Value Per Section:**

1.000 microfarads single section

**Nonderated Operating Temp:**

Between -55.0 degrees celsius and 85.0 degrees celsius

**Nonderated Continuous Voltage Rating And Type Per Section:**

35.0 dc single section

**Criticality Code Justification:**

Zzzy

**Tolerance Range Per Section:**

-20.00/+20.00 percent single section

**Case Material:**

Plastic

**Capacitive Electrode Material:**

Tantalum

**Terminal Surface Treatment:**

Solder

**Special Features:**

Item must comply with requirements of defense supply center columbus production standard no. Lo4184

**Terminal Type And Quantity:**

2 uninsulated wire lead

**Reference Number Differentiating Characteristics:**

Reference number differentiating material will be in accordance with naval inventory control point activity hx quality control. Manufacturing and testing specifications available at the dla icp

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A010b0