NSN 5910-01-316-9530

Electrolytic Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-316-9530

Body Style:
W/o mtg facilities, terminal (s) on one end
Reliability Indicator:
Not established
Terminal Length:
Between 0.155 inches and 0.219 inches
Body Diameter:
0.175 inches
Body Length:
0.340 inches
Center To Center Distance Between Terminals Parallel To Diameter:
0.250 inches
Terminal Diameter:
0.020 inches
Schematic Diagram Designator:
No common or grounded electrode (s)
Anode Type:
Solid
Electrical Polarization:
Polarized
End Application:
4920-01-125-2115 test system, aut
Capacitance Value Per Section:
0.100 microfarads single section
Nonderated Operating Temp:
Between -55.0 degrees celsius and 85.0 degrees celsius
Nonderated Continuous Voltage Rating And Type Per Section:
35.0 dc single section
Tolerance Range Per Section:
-10.00/+10.00 percent single section
Case Material:
Plastic
Capacitive Electrode Material:
Tantalum
Dissipation Factor At Reference Tempurature In Percent:
3.000
Dc Leakage At Reference Temp:
0.500 microamperes
Terminal Surface Treatment:
Solder
Terminal Type And Quantity:

2 uninsulated wire lead

NSN 5910-01-316-9530

Electrolytic Fixed Capacitor - Page 2 of 2



_					
c	hο	JIF.		.ife:	
J			_	.II C.	

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A010b0