## NSN 5910-01-317-3037

Paper-plastic Dielectric Metallized Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-317-3037

Rody	Style:	
Dogv	OLVIC.	

W/o mtg facilities, terminals on opposite surfaces

**Reliability Indicator:** 

Not established

**Terminal Length:** 

Between 1.500 inches and 2.500 inches

**Body Length:** 

Between 0.480 inches and 0.580 inches

**Body Width:** 

Between 0.070 inches and 0.170 inches

**Body Height:** 

Between 0.390 inches and 0.490 inches

**Terminal Diameter:** 

0.020 inches

**Schematic Diagram Designator:** 

No common or grounded electrode (s)

**Insulation Resistance At Maximum Operating Temp:** 

2000.0 megohm-microfarads

**Capacitance Value Per Section:** 

0.220 microfarads single section

**Nonderated Operating Temp:** 

Between -55.0 degrees celsius and 85.0 degrees celsius

Nonderated Continuous Voltage Rating And Type Per Section:

100.0 dc single section

**Tolerance Range Per Section:** 

-5.00/+5.00 percent single section

**Case Material:** 

Plastic

Insulation Resistance At Reference Temp:

20000.0 megohm-microfarads

**Dissipation Factor At Reference Tempurature In Percent:** 

1.000

**Terminal Surface Treatment:** 

Solder

**Dielectric Material:** 

Plastic polyethylene terephthalate

Terminal Type And Quantity:

2 uninsulated wire lead

Shelf Life:

N/a

**Unit Of Measure:** 

--

## NSN 5910-01-317-3037

Paper-plastic Dielectric Metallized Fixed Capacitor - Page 2 of 2



	atio	

No

Fiig:

A010b0