

View Online at <https://aerobasegroup.com/nsn/5910-01-317-6512>

Body Style:

W/o mtg facilities, terminal (s) on one end

Reliability Indicator:

Not established

Terminal Length:

0.250 inches

Body Diameter:

2.078 inches

Body Length:

5.750 inches

Center To Center Distance Between Terminals Parallel To Diameter:

Between 0.859 inches and 0.891 inches

Terminal Diameter:

0.190 inches

Schematic Diagram Designator:

No common or grounded electrode (s)

Anode Type:

Plain foil

Electrical Polarization:

Polarized

Capacitance Value Per Section:

14000.000 microfarads single section

Nonderated Operating Temp:

Between -40.0 degrees celsius and 85.0 degrees celsius

Dc Leakage At Maximum Operating Temp:

6000.0 microamperes

Nonderated Continuous Voltage Rating And Type Per Section:

100.0 dc single section

Criticality Code Justification:

Feat

Tolerance Range Per Section:

-10.00/+75.00 percent single section

Case Material:

Metal

Capacitive Electrode Material:

Aluminum

Equivalent Series Resistance At Reference Temperature In Ohms:

0.174

Dc Leakage At Reference Temp:

100.000 microamperes

Case Insulation Material:

Plastic

Special Features:

Item must comply with requirements of defense electronics supply center product1on standard no. L04228; for navy nuclear propulsion plant products only

Terminal Type And Quantity:

2 threaded hole

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A010b0