## NSN 5910-01-317-6512

Electrolytic Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-317-6512

· · · ·
Body Style:
W/o mtg facilities, terminal (s) on one end
Reliability Indicator:
Not established
Terminal Length:
0.250 inches
Body Diameter:
2.078 inches
Body Length:
5.750 inches
Center To Center Distance Between Terminals Parallel To Diameter
Between 0.859 inches and 0.891 inches
Terminal Diameter:
0.190 inches
Schematic Diagram Designator:
No common or grounded electrode (s)
Anode Type:
Plain foil
Electrical Polarization:
Polarized
Capacitance Value Per Section:
14000.000 microfarads single section
Nonderated Operating Temp:
Between -40.0 degrees celsius and 85.0 degrees celsius
Dc Leakage At Maximum Operating Temp:
6000.0 microamperes
Nonderated Continuous Voltage Rating And Type Per Section:
100.0 dc single section
Criticality Code Justification:
Feat
Tolerance Range Per Section:
-10.00/+75.00 percent single section
Case Material:
Metal
Capacitive Electrode Material:
Aluminum
Equivalent Series Resistance At Reference Tempurature In Ohms:
0.174
Dc Leakage At Reference Temp:
100.000 microamperes

Plastic

**Case Insulation Material:** 

## NSN 5910-01-317-6512

Electrolytic Fixed Capacitor - Page 2 of 2



## **Special Features:**

Item must comply with requirements of defense electronics supply center product1on standard no. L04228; for navy nuclear propulsion plant products only

## **Terminal Type And Quantity:**

2 threaded hole

Shelf Life:

N/a

**Unit Of Measure:** 

Demilitarization:

No

Fiig:

A010b0