

View Online at https://aerobasegroup.com/nsn/5910-01-318-3519

Body Style:	
Chip type	
Reliability Indicator:	
Not established	
Terminal Length:	
Between 0.005 inches and 0.015 inches	
Body Length:	
Between 0.030 inches and 0.080 inches	
Body Width:	
Between 0.040 inches and 0.070 inches	
Body Height:	
Between 0.028 inches and 0.057 inches	
Schematic Diagram Designator:	
No common or grounded electrode (s)	
End Application:	
Used on rt1360a and c-10776a	
Insulation Resistance At Maximum Operating Temp:	
10000.0 megohms	
Capacitance Value Per Section:	
2.700 picofarads single section	
Nonderated Operating Temp:	
Between -55.0 degrees celsius and 125.0 degrees celsius	
Tempurature Coefficient Of Capacitance Per Section In Ppm Per Deg Celsius:	
90.0 single section	
Nonderated Continuous Voltage Rating And Type Per Section:	
50.0 dc single section	
Tolerance Of Tempurature Coefficient Per Section In Ppm Per Deg Celsius:	
-20.0/+20.0 single section	
Tolerance Range Per Section:	
-0.25/+0.25 picofarads single section	
Case Material:	
Ceramic	
Insulation Resistance At Reference Temp:	
100000.0 megohms	
Dissipation Factor At Reference Tempurature In Percent:	
0.150	
Terminal Surface Treatment:	
Solder	
Terminal Type And Quantity:	
2 bonding pad	
Shelf Life:	
N/a	



Unit Of Measure:

Demilitarization:

No

Fiig:

A010b0