NSN 5910-01-318-5905

W/o mtg facilities, terminals on opposite surfaces

Body Style:

Reliability Indicator:

Not established

Terminal Length:

0.500 inches **Body Length:**1.900 inches **Body Width:**0.450 inches

Paper Dielectric Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-318-5905

| | Body Height: | | | | | |
|-----------------------------|--|--|--|--|--|--|
| | 1.470 inches | | | | | |
| | Distance Between Centerlines Of Mounting Facilities Parallel To Body Length: | | | | | |
| | 1.500 inches | | | | | |
| | Schematic Diagram Designator: | | | | | |
| | Feedthrough | | | | | |
| | Mounting Facility Screw Thread Series Designator: | | | | | |
| | Unc | | | | | |
| | Mounting Facility Type And Quantity: | | | | | |
| | 2 threaded mounting holes | | | | | |
| | Section Quantity: | | | | | |
| | 4 | | | | | |
| | Capacitance Value Per Section: | | | | | |
| | 0.150 microfarads all sections | | | | | |
| | Nonderated Operating Temp: | | | | | |
| | Between -55.0 degrees celsius and 100.0 degrees celsius | | | | | |
| ٠ | Thread Size: | | | | | |
| | 0.112 inches | | | | | |
| | Nonderated Continuous Voltage Rating And Type Per Section: | | | | | |
| ; | 300.0 dc all sections | | | | | |
| | Tolerance Range Per Section: | | | | | |
| | -15.00 to 15.00 percent all sections | | | | | |
| | Case Material: | | | | | |
| | Plastic | | | | | |
| | Insulation Resistance At Reference Temp: | | | | | |
| | 1000.0 megohms | | | | | |
| | Dissipation Factor At Reference Tempurature In Percent: | | | | | |
| | 0.010 | | | | | |
| Terminal Surface Treatment: | | | | | | |
| | Solder | | | | | |
| | Terminal Type And Quantity: | | | | | |
| | 8 solder stud and 4 tab, solder lug | | | | | |
| | | | | | | |

NSN 5910-01-318-5905

Paper Dielectric Fixed Capacitor - Page 2 of 2



| | | fe: |
|--|--|-----|
| | | |
| | | |

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A010b0