NSN 5910-01-319-1050

Ceramic Dielectric Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-319-1050 **Body Style: Dual inline Reliability Indicator:** Established Reliability Failure Rate Level In Percent: 0.100 **Body Length:** 0.260 inches **Body Width:** 0.092 inches **Body Height:** 0.128 inches **Schematic Diagram Designator:** No common or grounded electrode (s) **Capacitance Value Per Section:** 2.700 nanofarads single section **Voltage Tempurature Limits Per Section In Percent Capacitance Change:** -15.0/+15.0 without voltage applied single section **Nonderated Operating Temp:** Between -55.0 degrees celsius and 125.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 100.0 dc single section **Tolerance Range Per Section:** -10.00/+10.00 percent single section **Case Material: Plastic Insulation Resistance At Reference Temp:** 1000.0 megohm-microfarads **Dissipation Factor At Reference Tempurature In Percent:** 2.500 **Test Data Document:** 81349-mil-c-39014 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). **Terminal Type And Quantity:** 2 printed circuit **Specification Data:** 81349-mil-c-39014/22 government specification Shelf Life:

No

N/a

Unit Of Measure:

Demilitarization:

NSN 5910-01-319-1050

Ceramic Dielectric Fixed Capacitor - Page 2 of 2



Fiig:

A010b0