NSN 5910-01-319-9893

Paper-plastic Dielectric Metallized Fixed Capacitor - Page 1 of 2



| View Online at https://aerobasegroup.com/nsn/5910-01-319-9893 |
|---|
| Body Style: |
| W/o mtg facilities, axial terminals |
| Reliability Indicator: |
| Not established |
| Terminal Length: |
| 1.120 inches |
| Body Diameter: |
| 0.197 inches |
| Body Length: |
| 0.433 inches |
| Terminal Diameter: |
| 0.025 inches |
| Schematic Diagram Designator: |
| No common or grounded electrode (s) |
| Capacitance Value Per Section: |
| 0.047 microfarads single section |
| Nonderated Operating Temp: |
| Between -55.0 degrees celsius and 85.0 degrees celsius |
| Nonderated Continuous Voltage Rating And Type Per Section: |
| 250.0 dc single section |
| Criticality Code Justification: |
| Zzzy |
| Tolerance Range Per Section: |
| -5.00/+5.00 percent single section |
| Case Material: |
| Plastic |
| Insulation Resistance At Reference Temp: |
| 10000.0 megohms |
| Dissipation Factor At Reference Tempurature In Percent: |
| 1.500 |
| Terminal Surface Treatment: |
| Solder |
| Dielectric Material: |
| Plastic polyester |
| Special Features: |
| Item must comply with requirements of defense supply center columbus production standard no. Lo4245 |
| Terminal Type And Quantity: |
| 2 uninsulated wire lead |
| Reference Number Differentiating Characteristics: |
| Reference number differentiating material will be in accordance with naval inventory control point activity hx quality control. Manufacturing |
| and testing specifications available at the dla icp |

N/a

Shelf Life:

NSN 5910-01-319-9893

Paper-plastic Dielectric Metallized Fixed Capacitor - Page 2 of 2



| | | • - | | | | | | |
|---|-----|-----|----|-----|----|----|----|----|
| | In | | Of | RЛ | മാ | CI | ır | Δ. |
| L | ,,, | | | IVI | ca | | | |

--

Demilitarization:

No

Fiig:

A010b0