NSN 5910-01-320-7781



Electrolytic Fixed Capacitor - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5910-01-320-7781 **Body Style:** W/o mtg facilities, terminal (s) on one end Reliability Indicator: Not established **Terminal Length:** 0.787 inches **Body Diameter:** 0.315 inches **Body Length:** 0.354 inches **Center To Center Distance Between Terminals Parallel To Diameter:** 0.138 inches **Terminal Diameter:** 0.023 inches **Schematic Diagram Designator:** No common or grounded electrode (s) **Anode Type:** Plain foil **Impedance At Minimum Operating Tempurature In Ohms:** 3.0 **Electrical Polarization:** Polarized **End Application:** Communications restoral system an/tsc-115 **Capacitance Value Per Section:** 47.000 microfarads single section **Nonderated Operating Temp:** Between -40.0 degrees celsius and 85.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 50.0 dc single section **Tolerance Range Per Section:** -20.00/+20.00 percent single section **Case Material:** Metal **Capacitive Electrode Material:** Aluminum **Dissipation Factor At Reference Tempurature In Percent:** 10.000 Dc Leakage At Reference Temp:

3.000 microamperes

Terminal Surface Treatment:

Solder

NSN 5910-01-320-7781 Electrolytic Fixed Capacitor - Page 2 of 2



| Case insulation Material: |
|-----------------------------|
| Plastic |
| Terminal Type And Quantity: |
| 2 uninsulated wire lead |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| |

Fiig: A010b0