NSN 5910-01-321-9393

Plastic Dielectric Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-321-9393

Body	Stv	le٠
Bouv	JLV	ıc.

W/thd mtg hol (s)/stud(s) terminal(s) on one surface

Reliability Indicator:

Not established

Terminal Length:

Between 0.380 inches and 0.500 inches

Body Length:

6.000 inches

Body Width:

2.900 inches

Body Height:

4.250 inches

Center To Center Distance Between Terminals Parallel To Length:

4.500 inches

Terminal Diameter:

0.250 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

5.625 inches

Schematic Diagram Designator:

Electrod (s) grounded to case

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

2.500 inches

Internal Electrical Connection Type:

Extended foil

End Application:

5840-01-278-0160 transmitter gro

Mounting Facility Screw Thread Series Designator:

Unef

Mounting Facility Type And Quantity:

4 threaded mounting holes

Section Quantity:

,

Features Provided:

Hermetically sealed case

Capacitance Value Per Section:

5.000 microfarads all sections

Nonderated Operating Temp:

Between -46.0 degrees celsius and 71.0 degrees celsius

Thread Size:

0.250 inches

Nonderated Continuous Voltage Rating And Type Per Section:

600.0 ac-rms all sections

NSN 5910-01-321-9393

Plastic Dielectric Fixed Capacitor - Page 2 of 2



Tolerance Range Per Section:
-10.00/+10.00 percent single section
Case Material:
Metal
Dielectric Material:
Plastic
Terminal Type And Quantity:
8 threaded stud
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:

No Fiig: A010b0