NSN 5910-01-322-5912

Electrolytic Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-322-5912

Body Style:					
W/o mtg facilities, terminal (s) on one end					
Reliability Indicator:					
Not established					
Terminal Length:					
0.390 inches					
Body Diameter:					
0.400 inches					
Body Length:					
0.670 inches					
Center To Center Distance Between Terminals Parallel To Diameter:					
0.200 inches					
Terminal Diameter:					
0.020 inches					
Schematic Diagram Designator:					
No common or grounded electrode (s)					
Anode Type:					
Solid					
Electrical Polarization:					
Polarized					
Capacitance Value Per Section:					
47.000 microfarads single section					
Nonderated Operating Temp:					
Nonderated Operating Temp: Between -55.0 degrees celsius and 85.0 degrees celsius					
Between -55.0 degrees celsius and 85.0 degrees celsius					
Between -55.0 degrees celsius and 85.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section:					
Between -55.0 degrees celsius and 85.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 35.0 dc single section					
Between -55.0 degrees celsius and 85.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 35.0 dc single section Tolerance Range Per Section:					
Between -55.0 degrees celsius and 85.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 35.0 dc single section Tolerance Range Per Section: -10.00/+10.00 percent single section					
Between -55.0 degrees celsius and 85.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 35.0 dc single section Tolerance Range Per Section: -10.00/+10.00 percent single section Case Material:					
Between -55.0 degrees celsius and 85.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 35.0 dc single section Tolerance Range Per Section: -10.00/+10.00 percent single section Case Material: Plastic					
Between -55.0 degrees celsius and 85.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 35.0 dc single section Tolerance Range Per Section: -10.00/+10.00 percent single section Case Material: Plastic Capacitive Electrode Material:					
Between -55.0 degrees celsius and 85.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 35.0 dc single section Tolerance Range Per Section: -10.00/+10.00 percent single section Case Material: Plastic Capacitive Electrode Material: Tantalum					
Between -55.0 degrees celsius and 85.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 35.0 dc single section Tolerance Range Per Section: -10.00/+10.00 percent single section Case Material: Plastic Capacitive Electrode Material: Tantalum Dissipation Factor At Reference Tempurature In Percent:					
Between -55.0 degrees celsius and 85.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 35.0 dc single section Tolerance Range Per Section: -10.00/+10.00 percent single section Case Material: Plastic Capacitive Electrode Material: Tantalum Dissipation Factor At Reference Tempurature In Percent: 6.000					
Between -55.0 degrees celsius and 85.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 35.0 dc single section Tolerance Range Per Section: -10.00/+10.00 percent single section Case Material: Plastic Capacitive Electrode Material: Tantalum Dissipation Factor At Reference Tempurature In Percent: 6.000 Dc Leakage At Reference Temp:					
Between -55.0 degrees celsius and 85.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 35.0 dc single section Tolerance Range Per Section: -10.00/+10.00 percent single section Case Material: Plastic Capacitive Electrode Material: Tantalum Dissipation Factor At Reference Tempurature In Percent: 6.000 Dc Leakage At Reference Temp: 10.600 microamperes					
Between -55.0 degrees celsius and 85.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 35.0 dc single section Tolerance Range Per Section: -10.00/+10.00 percent single section Case Material: Plastic Capacitive Electrode Material: Tantalum Dissipation Factor At Reference Tempurature In Percent: 6.000 Dc Leakage At Reference Temp: 10.600 microamperes Terminal Surface Treatment:					
Between -55.0 degrees celsius and 85.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 35.0 dc single section Tolerance Range Per Section: -10.00/+10.00 percent single section Case Material: Plastic Capacitive Electrode Material: Tantalum Dissipation Factor At Reference Tempurature In Percent: 6.000 Dc Leakage At Reference Temp: 10.600 microamperes Terminal Surface Treatment: Solder					

N/a

NSN 5910-01-322-5912

Electrolytic Fixed Capacitor - Page 2 of 2



		• •			
ш	ın	10	<i>(</i>)+	Measure:	

--

Demilitarization:

No

Fiig:

A010b0