NSN 5910-01-323-6921

Ceramic Dielectric Variable Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-323-6921

Body Style:
Piston
Overall Length:
0.240 inches
Terminal Length:
0.100 inches
Body Length:
0.096 inches
Overall Diameter:
0.094 inches
Tempurature Coefficient Of Capacitance In Ppm Per Deg Celsius:
0.0 single section
Tolerance Of Tempurature Coefficient In Ppm Per Deg Celsius:
-50.0/+50.0 single section
Center To Center Distance Between Terminals Parallel To Length:
0.130 inches
Quality Factor At 25 Deg Celsius:
5000.0
Terminal Width:
0.040 inches
Terminal Thickness:
0.008 inches
Inclosure Type:
Encased
Adjustment Device Torque:
Between 0.100 inch-ounces and 1.000 inch-ounces
Insulation Dc Resistance At 25 Deg Celsius:
1000000.0 megohms
Insulation Dc Resistance At Max Operating Temp:
100000.0 megohms
Mounting Facility Type And Quantity:
2 terminal
Nonderated Operating Temp:
Between -55.0 degrees celsius and 125.0 degrees celsius
Capacitance Range In Picofarads:
+0.3/+1.2 single section
Nonderated Voltage Rating And Type:
500.0 dc continuous single section
Adjustment Device Drive Type And Quantity:
1 slotted screw
Test Data Document:
81349-mil-c-14409 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

NSN 5910-01-323-6921

Ceramic Dielectric Variable Capacitor - Page 2 of 2



Terminal Type And Quantity:
2 printed circuit
Specification Data:
81349-mil-c-14409/16 government specification
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:

A096a0