

View Online at <https://aerobasegroup.com/nsn/5910-01-324-5828>

**Body Style:**

W/o mtg facilities terminal (s) on one surface

**Reliability Indicator:**

Established

**Reliability Failure Rate Level In Percent:**

1.000

**Terminal Length:**

1.250 inches

**Body Length:**

Between 0.220 inches and 0.270 inches

**Body Width:**

Between 0.200 inches and 0.240 inches

**Body Height:**

Between 0.100 inches and 0.140 inches

**Center To Center Distance Between Terminals Parallel To Length:**

Between 0.185 inches and 0.215 inches

**Terminal Diameter:**

Between 0.024 inches and 0.029 inches

**Schematic Diagram Designator:**

No common or grounded electrode (s)

**End Application:**

1260-01-208-6448 mast mounted si

**Features Provided:**

Hermetically sealed case

**Insulation Resistance At Maximum Operating Temp:**

70000.0 megohms

**Capacitance Value Per Section:**

0.0047 microfarads single section

**Nonderated Operating Temp:**

Between -55.0 degrees celsius and 85.0 degrees celsius

**Nonderated Continuous Voltage Rating And Type Per Section:**

150.0 dc single section

**Tolerance Range Per Section:**

-1.00/+1.00 percent single section

**Case Material:**

Ceramic

**Insulation Resistance At Reference Temp:**

200000.0 megohms

**Dissipation Factor At Reference Temperature In Percent:**

0.200

**Terminal Surface Treatment:**

Solder

**Dielectric Material:**

Plastic polycarbonate

**Test Data Document:**

81349-mil-c-39022 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Terminal Type And Quantity:**

2 uninsulated wire lead

**Specification Data:**

81349-mil-c-39022/11 government specification

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A010b0