NSN 5910-01-324-7176

Paper-plastic Dielectric Metallized Fixed Capacitor - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5910-01-324-7176

Body Style:
W/o mtg facilities, axial terminals
Reliability Indicator:
Established
Reliability Failure Rate Level In Percent:
0.100
Terminal Length:
1.625 inches
Body Diameter:
0.290 inches
Body Length:
0.780 inches
Terminal Diameter:
0.020 inches
Schematic Diagram Designator:
No common or grounded electrode (s)
Capacitance Value Per Section:
0.680 microfarads single section
Nonderated Operating Temp:
Between -55.0 degrees celsius and 125.0 degrees celsius
Nonderated Continuous Voltage Rating And Type Per Section:
100.0 dc single section
Tolerance Range Per Section:
-10.00/+10.00 percent single section
Case Material:
Plastic
Insulation Resistance At Reference Temp:
100000.0 megohm-microfarads
Dissipation Factor At Reference Tempurature In Percent:
0.300
Terminal Surface Treatment:
Solder
Terminal Type And Quantity:
2 uninsulated wire lead
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
Yes - demil/mli
Fiig:

A010b0