## NSN 5910-01-325-1979

Electrolytic Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-325-1979

**Body Style:** W/o mtg facilities, terminal (s) on one end Reliability Indicator: Not established **Terminal Length:** 0.787 inches **Body Diameter:** 0.248 inches **Body Length:** 0.441 inches **Center To Center Distance Between Terminals Parallel To Diameter:** 0.095 inches **Terminal Diameter:** 0.020 inches **Schematic Diagram Designator:** No common or grounded electrode (s) **Anode Type:** Plain foil **Impedance At Minimum Operating Tempurature In Ohms:** 2.0 **Electrical Polarization:** Polarized **End Application:** Communication restoral system an/tsc-115 **Capacitance Value Per Section:** 100.000 microfarads single section **Nonderated Operating Temp:** Between -40.0 degrees celsius and 85.0 degrees celsius Dc Leakage At Maximum Operating Temp: 210.0 microamperes Nonderated Continuous Voltage Rating And Type Per Section: 50.0 dc single section **Tolerance Range Per Section:** -20.00/+20.00 percent single section **Case Material:** Metal **Capacitive Electrode Material:** Aluminum **Dissipation Factor At Reference Tempurature In Percent: Equivalent Series Resistance At Reference Tempurature In Ohms:** 

1.66

## NSN 5910-01-325-1979

Electrolytic Fixed Capacitor - Page 2 of 2



Dc Leakage At Reference Temps
50.000 microamperes
Terminal Surface Treatment:
Solder
Case Insulation Material:
Plastic
Terminal Type And Quantity:
2 uninsulated wire lead
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

**Fiig:** A010b0