## NSN 5910-01-326-7860

Paper-plastic Dielectric Metallized Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-326-7860

**Body Style:** W/o mtg facilities terminal (s) on one surface **Reliability Indicator:** Not established **Terminal Length:** 0.500 inches **Body Length:** 0.615 inches **Body Width:** 0.400 inches **Body Height:** 0.215 inches Center To Center Distance Between Terminals Parallel To Length: Between 0.485 inches and 0.515 inches **Terminal Diameter:** 0.025 inches **Schematic Diagram Designator:** No common or grounded electrode (s) **Features Provided:** Hermetically sealed case **Insulation Resistance At Maximum Operating Temp:** 10000.0 megohms **Capacitance Value Per Section:** 0.150 microfarads single section **Nonderated Operating Temp:** Between -55.0 degrees celsius and 125.0 degrees celsius Tempurature Coefficient Of Capacitance Per Section In Ppm Per Deg Celsius: -2.5 single section Nonderated Continuous Voltage Rating And Type Per Section: 50.0 dc single section **Tolerance Of Tempurature Coefficient Per Section In Ppm Per Deg Celsius:** -2.0/+2.0 single section **Tolerance Range Per Section:** -1.00/+1.00 percent single section **Case Material:** Metal **Insulation Resistance At Reference Temp:** 100000.0 megohms **Dissipation Factor At Reference Tempurature In Percent:** 0.150

Solder

**Terminal Surface Treatment:** 

## NSN 5910-01-326-7860

Paper-plastic Dielectric Metallized Fixed Capacitor - Page 2 of 2



Dielectric Material:
Plastic polycarbonate
Terminal Type And Quantity:
2 uninsulated wire lead
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A010b0