## NSN 5910-01-327-3532

Paper-plastic Dielectric Metallized Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-327-3532

Body	Styl	e:

W/o mtg facilities terminal (s) on one surface

**Reliability Indicator:** 

Not established

**Terminal Length:** 

0.500 inches

**Body Length:** 

Between 0.410 inches and 0.430 inches

**Body Width:** 

0.300 inches

**Body Height:** 

Between 0.170 inches and 0.190 inches

Center To Center Distance Between Terminals Parallel To Length:

Between 0.285 inches and 0.315 inches

**Terminal Diameter:** 

0.025 inches

**Schematic Diagram Designator:** 

No common or grounded electrode (s)

**End Application:** 

6625-01-284-8256 meter modulation

**Insulation Resistance At Maximum Operating Temp:** 

50.0 megohm-microfarads

**Capacitance Value Per Section:** 

0.002 microfarads single section

**Nonderated Operating Temp:** 

Between -55.0 degrees celsius and 125.0 degrees celsius

Nonderated Continuous Voltage Rating And Type Per Section:

50.0 dc single section

**Tolerance Range Per Section:** 

-2.00/+2.00 percent single section

**Case Material:** 

Plastic

**Insulation Resistance At Reference Temp:** 

25000.0 megohm-microfarads

**Dissipation Factor At Reference Tempurature In Percent:** 

0.300

**Terminal Surface Treatment:** 

Solder

**Dielectric Material:** 

Plastic polycarbonate

**Terminal Type And Quantity:** 

2 uninsulated wire lead

## NSN 5910-01-327-3532

Paper-plastic Dielectric Metallized Fixed Capacitor - Page 2 of 2



Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:

A010b0