NSN 5910-01-329-4363

Ceramic Dielectric Variable Capacitor - Page 1 of 1



| View Online at https://aerobasegroup.com/nsn/5910-01-329-4363 |
|---|
| Body Style: |
| Rotary |
| Terminal Length: |
| 0.125 inches |
| Overall Height: |
| 0.218 inches |
| Overall Diameter: |
| 0.218 inches |
| Center To Center Distance Between Terminals Parallel To Diameter: |
| 0.200 inches |
| Center To Center Distance Between Mounting Facilities Parallel To Diameter: |
| 0.200 inches |
| End Application: |
| Calibration standards equipment, general puepose electronic test equipment, yellowstone class ad-41 |
| Inclosure Type: |
| Encased |
| Mounting Facility Type And Quantity: |
| 2 terminal |
| Nonderated Operating Temp: |
| Between -55.0 degrees celsius and 125.0 degrees celsius |
| Capacitance Range In Picofarads: |
| +6.0/+22.0 single section |
| Nonderated Voltage Rating And Type: |
| 63.0 dc continuous single section |
| Capacitance Change In Percent At Operating Tempurature From 25 Deg Celsius: |
| -15.00/+16.00 single section |
| Adjustment Device Drive Type And Quantity: |
| 1 slotted screw |
| Material: |
| Ceramic base |
| Terminal Type And Quantity: |
| 2 pin |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| A096a0 |