NSN 5910-01-331-7584

Plastic Dielectric Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-331-7584

Body Style:

W/o mtg facilities, terminal (s) on one surface

Reliability Indicator:

Not established

Terminal Length:

Between 1.000 inches and 1.500 inches

Body Length:

Between 0.540 inches and 0.560 inches

Body Width:

Between 0.240 inches and 0.260 inches

Body Height:

Between 0.455 inches and 0.485 inches

Center To Center Distance Between Terminals Parallel To Length:

Between 0.395 inches and 0.405 inches

Terminal Diameter:

Between 0.024 inches and 0.026 inches

Schematic Diagram Designator:

No common or grounded electrode (s)

Features Provided:

Hermetically sealed case

Insulation Resistance At Maximum Operating Temp:

60000.0 megohms

Capacitance Value Per Section:

22000.000 picofarads single section

Nonderated Operating Temp:

Between -55.0 degrees celsius and 125.0 degrees celsius

Tempurature Coefficient Of Capacitance Per Section In Ppm Per Deg Celsius:

-200.0 single section

Nonderated Continuous Voltage Rating And Type Per Section:

50.0 dc single section

Tolerance Of Tempurature Coefficient Per Section In Ppm Per Deg Celsius:

-30.0/+30.0 single section

Tolerance Range Per Section:

-5.00/+5.00 percent single section

Case Material:

Plastic

Insulation Resistance At Reference Temp:

600000.0 megohms

Dissipation Factor At Reference Tempurature In Percent:

0.300

Terminal Surface Treatment:

Solder

NSN 5910-01-331-7584

Plastic Dielectric Fixed Capacitor - Page 2 of 2



ח	iel	ectr	ic.	Mate	ria	ŀ
_		COL		matt	,ı ıu	

Plastic polyparaxylene

Terminal Type And Quantity:

2 uninsulated wire lead

Shelf Life:

N/a

Unit Of Measure:

__

Demilitarization:

No

Fiig:

A010b0