

View Online at <https://aerobasegroup.com/nsn/5910-01-332-5621>

**Body Style:**

W/thd mtg bushing, terminals on opposite ends

**Reliability Indicator:**

Not established

**Width Across Flats:**

Between 0.177 inches and 0.197 inches

**Unable To Decode:**

Unable to decode and unable to decode

**Terminal Length:**

Between 0.493 inches and 0.555 inches

**Unable To Decode:**

Unable to decode and unable to decode

**Body Length:**

Between 0.349 inches and 0.369 inches

**Continuous Current Rating In Amps:**

10.0

**Terminal Diameter:**

Between 0.030 inches and 0.034 inches

**Schematic Diagram Designator:**

Feedthrough

**Mounting Facility Screw Thread Series Designator:**

Unc

**Mounting Facility Type And Quantity:**

1 threaded bushing

**Capacitance Value Per Section:**

0.027 microfarads single section

**Nonderated Operating Temp:**

Between -55.0 degrees celsius and 125.0 degrees celsius

**Thread Size:**

0.164 inches

**Nonderated Continuous Voltage Rating And Type Per Section:**

100.0 dc single section

**Criticality Code Justification:**

Feat

**Tolerance Range Per Section:**

-0.00/+100.00 percent single section

**Case Material:**

Metal

**Insulation Resistance At Reference Temp:**

500.0 megohms

**Terminal Surface Treatment:**

Solder

**Special Features:**

Nuclear hardness critical item

**Terminal Type And Quantity:**

1 solder stud and 1 uninsulated wire lead

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A010b0