

View Online at <https://aerobasegroup.com/nsn/5910-01-332-5624>

**Body Style:**

W/o mtg facilities, terminal (s) on one end

**Reliability Indicator:**

Not established

**Terminal Length:**

Between 0.120 inches and 0.240 inches

**Body Diameter:**

0.200 inches

**Body Length:**

0.410 inches

**Center To Center Distance Between Terminals Parallel To Diameter:**

Between 0.180 inches and 0.220 inches

**Terminal Diameter:**

Between 0.018 inches and 0.022 inches

**Schematic Diagram Designator:**

No common or grounded electrode (s)

**Anode Type:**

Solid

**Impedance At Minimum Operating Temperature In Ohms:**

3.2

**Electrical Polarization:**

Polarized

**Capacitance Value Per Section:**

10.000 microfarads single section

**Nonderated Operating Temp:**

Between -55.0 degrees celsius and 85.0 degrees celsius

**Nonderated Continuous Voltage Rating And Type Per Section:**

16.0 dc single section

**Tolerance Range Per Section:**

-10.00/+10.00 percent single section

**Case Material:**

Plastic

**Capacitive Electrode Material:**

Tantalum

**Dissipation Factor At Reference Temperature In Percent:**

0.080

**Dc Leakage At Reference Temp:**

1.200 microamperes

**Terminal Surface Treatment:**

Solder

**Terminal Type And Quantity:**

2 uninsulated wire lead

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A010b0