## NSN 5910-01-332-9284

Ceramic Dielectric Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-332-9284

Bod	У	St	yle:
W/o	m	ıtg	fac

W/o mtg facilities terminal (s) on one surface

**Reliability Indicator:** 

Not established

**Terminal Length:** 

1.250 inches

**Body Length:** 

0.570 inches

**Body Width:** 

0.500 inches

Body Height:

0.270 inches

**Center To Center Distance Between Terminals Parallel To Length:** 

Between 0.445 inches and 0.505 inches

**Terminal Diameter:** 

Between 0.023 inches and 0.027 inches

**Schematic Diagram Designator:** 

No common or grounded electrode (s)

**Insulation Resistance At Maximum Operating Temp:** 

10000.0 megohms

**Capacitance Value Per Section:** 

0.100 microfarads single section

**Voltage Tempurature Limits Per Section In Percent Capacitance Change:** 

-15.0/+15.0 without voltage applied single section

**Nonderated Operating Temp:** 

Between -55.0 degrees celsius and 125.0 degrees celsius

Nonderated Continuous Voltage Rating And Type Per Section:

1000.0 dc single section

**Tolerance Range Per Section:** 

-10.00/+10.00 percent single section

**Case Material:** 

Plastic

**Insulation Resistance At Reference Temp:** 

100000.0 megohms

**Dissipation Factor At Reference Tempurature In Percent:** 

2.500

**Terminal Surface Treatment:** 

Solder

**Terminal Type And Quantity:** 

2 uninsulated wire lead

Shelf Life:

N/a

## NSN 5910-01-332-9284

Ceramic Dielectric Fixed Capacitor - Page 2 of 2



		• •			
ш	ın	10	<i>(</i> )+	Measure:	

--

Demilitarization:

No

Fiig:

A010b0