NSN 5910-01-332-9298

Paper-plastic Dielectric Metallized Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-332-9298

Body Style:
W/o mtg facilities, terminal (s) on one surface
Reliability Indicator:
Not established
Terminal Length:
Between 0.157 inches and 0.236 inches
Body Length:
1.020 inches
Body Width:
0.295 inches
Body Height:
0.650 inches
Center To Center Distance Between Terminals Parallel To Length
Between 0.870 inches and 0.902 inches
Terminal Diameter:
0.032 inches
Schematic Diagram Designator:
No common or grounded electrode (s)
End Application:
6625-01-196-8335 test set, electr
Capacitance Value Per Section:
0.330 microfarads single section
Nonderated Operating Temp:
Between -55.0 degrees celsius and 85.0 degrees celsius
Nonderated Continuous Voltage Rating And Type Per Section:
400.0 dc single section
Tolerance Range Per Section:
-5.00/+5.00 percent single section
Case Material:
Plastic
Insulation Resistance At Reference Temp:
10000.0 megohms
Dissipation Factor At Reference Tempurature In Percent:
0.500
Terminal Surface Treatment:
Solder
Dielectric Material:
Plastic polycarbonate
Terminal Type And Quantity:
2 uninsulated wire lead
Shalf Life:

N/a

NSN 5910-01-332-9298

Paper-plastic Dielectric Metallized Fixed Capacitor - Page 2 of 2



		• -						
ш	ın	ıt (r 1t	ΝЛ	മാ	CI.	ıre:	•

--

Demilitarization:

No

Fiig:

A010b0