## NSN 5910-01-333-2141

Electrolytic Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-333-2141
Body Style:
W/o mtg facilities, terminal (s) on one end
Reliability Indicator:
Not established
Terminal Length:
0.155 inches
Body Diameter:
0.236 inches
Body Length:
0.400 inches
Center To Center Distance Between Terminals Parallel To Diameter:
0.200 inches
Terminal Diameter:
0.025 inches
Schematic Diagram Designator:
No common or grounded electrode (s)
Anode Type:
Solid
Impedance At Minimum Operating Tempurature In Ohms:
250.0
Electrical Polarization:
Polarized
End Application:
6625-01-196-8335 test set, electr
Capacitance Value Per Section:
6.800 microfarads single section
Nonderated Operating Temp:
Between -55.0 degrees celsius and 125.0 degrees celsius
Nonderated Continuous Voltage Rating And Type Per Section:
35.0 dc single section
Tolerance Range Per Section:
-10.00/+10.00 percent single section
Case Material:
Plastic
Capacitive Electrode Material:
Tantalum
Dissipation Factor At Reference Tempurature In Percent:
6.000
Dc Leakage At Reference Temp:
5.000 microamperes
Torminal Surface Treatment

Solder

## NSN 5910-01-333-2141

Electrolytic Fixed Capacitor - Page 2 of 2



Terminal Type And Quantity:
-----------------------------

2 uninsulated wire lead

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A010b0