## NSN 5910-01-333-2142



Electrolytic Fixed Capacitor - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5910-01-333-2142 **Body Style:** W/o mtg facilities, terminal (s) on one end Reliability Indicator: Not established **Terminal Length:** 0.155 inches **Body Diameter:** 0.340 inches **Body Length:** 0.492 inches **Center To Center Distance Between Terminals Parallel To Diameter:** 0.250 inches **Terminal Diameter:** 0.025 inches **Schematic Diagram Designator:** No common or grounded electrode (s) **Anode Type:** Solid **Electrical Polarization:** Polarized **End Application:** 6625-01-196-8335 test set, electr **Capacitance Value Per Section:** 68.000 microfarads single section **Nonderated Operating Temp:** Between -55.0 degrees celsius and 125.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 20.0 dc single section **Tolerance Range Per Section:** -10.00/+10.00 percent single section Case Material: **Plastic Capacitive Electrode Material: Tantalum Dissipation Factor At Reference Tempurature In Percent:** 8.000 Dc Leakage At Reference Temp:

7.000 microamperes **Terminal Surface Treatment:** Solder **Terminal Type And Quantity:** 2 uninsulated wire lead

## NSN 5910-01-333-2142

Electrolytic Fixed Capacitor - Page 2 of 2



_					
c	hο	JIF.		.ife:	
J			_	.II C.	

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A010b0