## NSN 5910-01-333-2409

Ceramic Dielectric Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-333-2409

**Body Style:** 

W/o mtg facilities, axial terminals

Reliability Indicator:

Not established

**Terminal Length:** 

0.100 inches

**Body Diameter:** 

Between 0.146 inches and 0.166 inches

**Body Length:** 

Between 0.100 inches and 0.120 inches

**Terminal Diameter:** 

0.030 inches

**Schematic Diagram Designator:** 

Feedthrough

**Insulation Resistance At Maximum Operating Temp:** 

500.0 megohms

**Capacitance Value Per Section:** 

100.000 picofarads single section

**Nonderated Operating Temp:** 

Between -55.0 degrees celsius and 125.0 degrees celsius

Tempurature Coefficient Of Capacitance Per Section In Ppm Per Deg Celsius:

0.0 single section

Nonderated Continuous Voltage Rating And Type Per Section:

200.0 dc single section

**Tolerance Of Tempurature Coefficient Per Section In Ppm Per Deg Celsius:** 

-20.0/+20.0 single section

**Tolerance Range Per Section:** 

-20.00/+60.00 percent single section

Case Material:

Metal

Insulation Resistance At Reference Temp:

50000.0 megohms

**Dissipation Factor At Reference Tempurature In Percent:** 

3.000

**Terminal Surface Treatment:** 

Gold

**Precious Material And Location:** 

Terminal surfaces and body surface gold

**Terminal Type And Quantity:** 

2 uninsulated wire lead

Shelf Life:

N/a

## NSN 5910-01-333-2409

Ceramic Dielectric Fixed Capacitor - Page 2 of 2



ш	ın	10	<i>(</i> )+	Measure:	

--

Demilitarization:

No

Fiig:

A010b0