NSN 5910-01-333-3253

Electrolytic Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-333-3253

Body Style:
W/o mtg facilities, terminal (s) on one end
Reliability Indicator:
Not established

0.218 inches

Body Diameter:

Terminal Length:

Between 1.978 inches and 2.178 inches

Body Length:

3.190 inches

Center To Center Distance Between Terminals Parallel To Diameter:

Between 0.859 inches and 0.891 inches

Terminal Diameter:

0.190 inches

Schematic Diagram Designator:

No common or grounded electrode (s)

Anode Type:

Plain foil

Impedance At Minimum Operating Tempurature In Ohms:

0.36

Electrical Polarization:

Polarized

Features Provided:

Burn in

Capacitance Value Per Section:

3900.000 microfarads single section

Nonderated Operating Temp:

Between -55.0 degrees celsius and 85.0 degrees celsius

Dc Leakage At Maximum Operating Temp:

4620.0 microamperes

Nonderated Continuous Voltage Rating And Type Per Section:

75.0 dc single section

Tolerance Range Per Section:

-10.00/+50.00 percent single section

Case Material:

Metal

Capacitive Electrode Material:

Aluminum

Equivalent Series Resistance At Reference Tempurature In Ohms:

0 031

Dc Leakage At Reference Temp:

770.000 microamperes

NSN 5910-01-333-3253

Electrolytic Fixed Capacitor - Page 2 of 2



Case insulation Material:
Plastic
Terminal Type And Quantity
2 threaded hole
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A010b0