## NSN 5910-01-334-1325

Paper-plastic Dielectric Metallized Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-334-1325

| Body Style:   |
|---|
| W/o mtg facilities terminal (s) on one surface                  |
| Reliability Indicator:  |
| Not established   |
| Terminal Length:  |
| 6.0 millimeters   |
| Body Length:  |
| 4.6 millimeters   |
| Body Width:   |
| 7.5 millimeters   |
| Body Height:  |
| 3.0 millimeters   |
| Center To Center Distance Between Terminals Parallel To Length: |
| 2.5 millimeters   |
| Terminal Diameter:  |
| 0.4 millimeters   |
| Schematic Diagram Designator:                                   |
| No common or grounded electrode (s)                             |
| Capacitance Value Per Section:                                  |
| 1000.000 picofarads single section                              |
| Nonderated Operating Temp:                                      |
| Between -55.0 degrees celsius and 100.0 degrees celsius         |
| Nonderated Continuous Voltage Rating And Type Per Section:      |
| 63.0 dc single section  |
| Tolerance Range Per Section:                                    |
| -10.00/+10.00 percent single section                            |
| Case Material:  |
| Plastic   |
| Insulation Resistance At Reference Temp:                        |
| 1000.0 megohms  |
| Terminal Surface Treatment:                                     |
| Solder  |
| Dielectric Material:  |
| Plastic polyethylene terephthalate                              |
| Terminal Type And Quantity:                                     |
| 2 uninsulated wire lead   |
| Shelf Life:   |
| N/a   |
| Unit Of Measure:  |
| <del></del>   |
| Demilitarization:   |

No

## NSN 5910-01-334-1325

Paper-plastic Dielectric Metallized Fixed Capacitor - Page 2 of 2



Fiig:

A010b0