

View Online at <https://aerobasegroup.com/nsn/5910-01-334-9675>

Body Style:

W/thd mtg bushing, terminals on opposite ends

Reliability Indicator:

Not established

Width Across Flats:

Between 0.177 inches and 0.197 inches

Unable To Decode:

Unable to decode and unable to decode

Terminal Length:

Between 0.593 inches and 0.655 inches

Unable To Decode:

Unable to decode and unable to decode

Body Length:

0.359 inches

Terminal Diameter:

0.032 inches

Schematic Diagram Designator:

Feedthrough

Mounting Facility Screw Thread Series Designator:

Unc

Mounting Facility Type And Quantity:

1 threaded bushing

Features Provided:

Mounting hardware

Capacitance Value Per Section:

0.005 microfarads single section

Nonderated Operating Temp:

Between -55.0 degrees celsius and 125.0 degrees celsius

Thread Size:

0.164 inches

Nonderated Continuous Voltage Rating And Type Per Section:

200.0 dc single section

Tolerance Range Per Section:

-0.00/+100.00 percent single section

Case Material:

Metal

Insulation Resistance At Reference Temp:

500.0 megohms

Dissipation Factor At Reference Temperature In Percent:

2.500

Terminal Surface Treatment:

Solder

Terminal Type And Quantity:

1 solder stud and 1 uninsulated wire lead

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A010b0