## NSN 5910-01-334-9675

Ceramic Dielectric Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-334-9675

**Body Style:** 

W/thd mtg bushing, terminals on opposite ends

Reliability Indicator:

Not established

Width Across Flats:

Between 0.177 inches and 0.197 inches

**Unable To Decode:** 

Unable to decode and unable to decode

**Terminal Length:** 

Between 0.593 inches and 0.655 inches

**Unable To Decode:** 

Unable to decode and unable to decode

**Body Length:** 

0.359 inches

**Terminal Diameter:** 

0.032 inches

**Schematic Diagram Designator:** 

Feedthrough

**Mounting Facility Screw Thread Series Designator:** 

Unc

**Mounting Facility Type And Quantity:** 

1 threaded bushing

Features Provided:

Mounting hardware

**Capacitance Value Per Section:** 

0.005 microfarads single section

**Nonderated Operating Temp:** 

Between -55.0 degrees celsius and 125.0 degrees celsius

**Thread Size:** 

0.164 inches

Nonderated Continuous Voltage Rating And Type Per Section:

200.0 dc single section

**Tolerance Range Per Section:** 

-0.00/+100.00 percent single section

**Case Material:** 

Metal

Insulation Resistance At Reference Temp:

500.0 megohms

**Dissipation Factor At Reference Tempurature In Percent:** 

2.500

**Terminal Surface Treatment:** 

Solder

## NSN 5910-01-334-9675

Ceramic Dielectric Fixed Capacitor - Page 2 of 2



	Ī	erminal	Type	And	Quantit	y:
--	---	---------	------	-----	---------	----

1 solder stud and 1 uninsulated wire lead

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A010b0