NSN 5910-01-335-1637

Electrolytic Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-335-1637

Body Style:

W/o mtg facilities, terminal (s) on one end

Reliability Indicator:

Not established

Terminal Length:

Between 0.155 inches and 0.219 inches

Body Diameter:

Between 0.225 inches and 0.275 inches

Body Length:

0.500 inches

Center To Center Distance Between Terminals Parallel To Diameter:

Between 0.110 inches and 0.140 inches

Terminal Diameter:

Between 0.018 inches and 0.022 inches

Schematic Diagram Designator:

No common or grounded electrode (s)

Anode Type:

Solid

Electrical Polarization:

Polarized

End Application:

5865-01-188-3309 jammer system, respo

Capacitance Value Per Section:

10.000 microfarads single section

Nonderated Operating Temp:

Between -55.0 degrees celsius and 85.0 degrees celsius

Nonderated Continuous Voltage Rating And Type Per Section:

6.0 dc single section

Tolerance Range Per Section:

-10.00/+10.00 percent single section

Case Material:

Plastic

Capacitive Electrode Material:

Tantalum

Dissipation Factor At Reference Tempurature In Percent:

8.000

Dc Leakage At Reference Temp:

1.000 microamperes

Terminal Surface Treatment:

Solder

Terminal Type And Quantity:

2 uninsulated wire lead

NSN 5910-01-335-1637

Electrolytic Fixed Capacitor - Page 2 of 2



		ife:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A010b0